

# edesa


CONVENTIONAL EXTRACTOR HOODS



## ECS-61110 X

Cod. 932271945

EAN 8422248350976



### GENERAL INFORMATION

|           |               |
|-----------|---------------|
| EAN/UPC   | 8422248350976 |
| Subfamily | Conventional  |

### Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

|   |       |
|---|-------|
| AEC (Annual energy consumption) (kWh/year)    | 45,1  |
| EEL class (energy efficiency class)           | C     |
| FDE (fluid dynamic efficiency)                | 9,4   |
| FDE class (fluid dynamic efficiency class)    | E     |
| LE (light efficiency) (lux/W)                 | 15,3  |
| LE class (light efficiency class)             | D     |
| GFE (grease filtering efficiency)             | 79,6  |
| GFE class (grease filtering efficiency class) | C     |
| Airflow in normal mode MIN (m3/h)             | 107,5 |
| Airflow in normal mode MAX (m3/h)             | 293,2 |
| Acoustic power in normal mode MIN (dB)        | 56    |
| Acoustic power in normal mode MAX (dB)        | 69    |
| Po (energy consumption in off mode) (W)       | 0     |
| Ps (energy consumption in standby mode) (W)   | 0     |

### Integration directive EU 66/2014

|  |       |
|--|-------|
| f (time increase factor)                                   | 1,7   |
| EEL (Energy Efficiency Index)                              | 82,4  |
| QBEP (maximum efficiency at air flow point) (m3/h)         | 116,2 |
| PBEP (maximum efficiency at pressure point) (Pa)           | 192   |
| WBEP (power consumption at maximum efficiency) (W)         | 66,2  |
| WL (nominal power lighting system) (W)                     | 5,5   |
| EMIDDLE (Average illuminance on the cooking surface) (lux) | 84,4  |

### External Dimensions

|                         |     |
|-------------------------|-----|
| Width (mm)              | 600 |
| Depth (mm)              | 452 |
| Diamètre de sortie (mm) | 120 |

### Characteristics

|                                       |                          |
|---------------------------------------|--------------------------|
| Motor quantity                        | 1                        |
| Motor model                           | L1N                      |
| Filter technology                     | Aluminium mesh           |
| Control technology                    | Mechanical rocker switch |
| Booster                               | -                        |
| Power levels                          | 3                        |
| Timer                                 | -                        |
| Filter saturation indicator           | -                        |
| Charcoal filter replacement indicator | -                        |
| Dimmer function                       | -                        |
| Connectivity                          | No                       |
| Remote control                        | -                        |
| Display                               | -                        |

### Lighting

|                |     |
|----------------|-----|
| Ray technology | LED |
|----------------|-----|

### Installation

|   |     |
|---|-----|
| Minimum distance to electric plate (mm) | 650 |
| Minimum distance to gas plate (mm)      | 650 |
| Recirculation option                    | -   |
| Charcoal filter                         | -   |
| Back draught shutter                    | No  |
| Inner shield                            | -   |

### Electric connection

|                           |         |
|---------------------------|---------|
| Nominal voltage (V)       | 220-240 |
| Nominal frequency (Hz)    | 50      |
| Nominal input power (W)   | 707,5   |
| Electric shock protection | Class I |
| Power cord length (m)     | 0,7     |
| Plug type                 | No plug |

