

edesa


CONVENTIONAL EXTRACTOR HOODS



ECS-61110 X

Cod. 932271945

EAN 8422248350976



GENERAL INFORMATION

EAN/UPC	8422248350976
Subfamily	Conventional

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	45,1
EI class (energy efficiency class)	C
FDE (fluid dynamic efficiency)	9,4
FDE class (fluid dynamic efficiency class)	E
LE (light efficiency) (lux/W)	15,3
LE class (light efficiency class)	D
GFE (grease filtering efficiency)	79,6
GFE class (grease filtering efficiency class)	C
Airflow in normal mode MIN (m3/h)	107,5
Airflow in normal mode MAX (m3/h)	293,2
Acoustic power in normal mode MIN (dB)	56
Acoustic power in normal mode MAX (dB)	69
Po (energy consumption in off mode) (W)	0
Ps (energy consumption in standby mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	1,7
EI (Energy Efficiency Index)	82,4
QBEP (maximum efficiency at air flow point) (m3/h)	116,2
PBEP (maximum efficiency at pressure point) (Pa)	192
WBEP (power consumption at maximum efficiency) (W)	66,2
WL (nominal power lighting system) (W)	5,5
EMIDDLE (Average illuminance on the cooking surface) (lux)	84,4

External Dimensions

Width (mm)	600
Depth (mm)	452
Diamètre de sortie (mm)	120

Characteristics

Motor quantity	1
Motor model	L1N
Filter technology	Aluminium mesh
Control technology	Mechanical rocker switch
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	No
Remote control	-
Display	-

Lighting

Ray technology	LED
----------------	-----

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	-
Charcoal filter	-
Back draught shutter	No
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	707,5
Electric shock protection	Class I
Power cord length (m)	0,7
Plug type	No plug

