

Code
EAN
Finish
Product fiche according to 2016/426/AB
Trade mark
Model
Adjusted Gas Type
Auxillary Burner Gas Power for G20-20mbar
Auxillary Burner Gas Consumption for G20-20mbar
Dia of Injector for Auxillary Burner
Semi Rapid Burner Gas Power for G20-20mbar
Semi Rapid Burner Gas Consumption for G20-20mbar
Dia of Injector for Semi Rapid Burner
Rapid Burner Gas Power for G20-20mbar
Rapid Burner Gas Consumption for G20-20mbar
Dia of Injector for Rapid Burner
Semi Rapid Burner Gas Power for G20-20mbar
Semi Rapid Burner Gas Consumption for G20-20mbar
Dia of Injector for Semi Rapid Burner
Wok Burner Gas Power for G20-20mbar
Wok Gas Consumption for G20-20mbar
Dia of Injector for WokBurner
Changeble Gas Type
Auxillary Burner Gas Power for G30-29mbar
Total Gas Power for G30-29mbar
Dia of Injector for Auxillary Burner
Semi Rapid Burner Gas Power for G30-29mbar
Semi Rapid Burner Gas Consumption for G30-29mbar
Dia of Injector for Semi Rapid Burner
Rapid Burner Gas Power for G30-29mbar
Rapid Burner Gas Consumption for G30-29mbar
Dia of Injector for Rapid Burner
Semi Rapid Burner Gas Power for G30-29mbar
Semi Rapid Burner Gas Consumption for G30-29mbar
Dia of Injector for Semi Rapid Burner
Wok Burner Gas Power for G20-90mbar
Wok Gas Consumption for G20-29mbar
Dia of Injector for WokBurner
Total Gas Power For G20-20mbar
Total Gas Consumption for G20-20mbar
Total Gas Power For G30-29mbar
Total Gas Consumption For G30-29mbar
Control panel
Display / LED
Knob Type
Knob Position
Functions

Pan Support
Packing Type
Packing materials
Burner Taps
Auxillary burner burner taps
Semi Rapid burner burner taps
Rapid burner burner taps
Wok burner burner taps
Burner Position
Right back
Right Front
Left back
Left Front
Middle Back
Middle Front
Safety
Flame Flaiure Device
Product dimensons (without box)
Height min/max [mm] Max (from under the galvanise base to top of the pan support) mm Min (form under the surface to top of the pan support) mm
Bench diameters (mm)
Width [mm]
Depth [mm]
Product Dimensions (with box)
Minimum cabinet height [mm]
Minimum cabinet width [mm]
Minimum cabinet depth [mm]
Power and water connection
Voltage range [V]
Frecuency [Hz]
Rated power [W]
Type of plug
Power cord length [mm]

922272069
8422248198332
Glass
EDESA
EGG-6041 TI TR CI N
G20-20 mbar
1.00 kW HS
0.095 m ³ /h
0.72 mm
1.75 kW. Hs
0.166 m ³ /h
0.97 mm
3.00 kW. Hs
0.238 m ³ /h
1.15 mm
N/A
N/A
N/A
4.00 kW.Hs
0.381 m ³ /h
1.50 mm
1.00 kW. Hs
72.713 g/h
0.50 mm
1.75 kW.Hs
127.248 g/h
0.65 mm
3.00 kW. Hs
181.783 g/h
0.85 mm
N/A
N/A
N/A
4.00 kW.Hs
291 g/h
1.00 mm
9.75 kW. Hs
0.880 m ³ /h
9.75 kW. Hs
672.744 g/g
none
Black
Front Controlled

Cast Iron Pan Support
Craft Carton
Straphore foam, carton box
2 mm enammel coated metal
2 mm enammel coated metal
2 mm enammel coated metal
2 mm enammel coated metal
Semi Rapid
Auxillary
Rapid
Wok
N/A
N/A
Yes
Max: 87.5 mm Min: 43.5 mm
560x490 mm
580 mm
520 mm
68 cm
61 cm
17 cm
220-240 V
50-60 Hz
0.6 W
No plug
3x0,75x1000 mm